



- Class AB power amplifier full MOSFET
- Unregulated power supply
- High level input with autosense power-on
- Cross Over with switchable High Pass or Low Pass filter
- Slot for G\_cards
- Remote Volume Control RTC (optional)

#### POWER SUPPLY

Power supply voltage	11 - 16V
DC-DC converter typology	Unregulated – Push Pull
Internal fuse	2 x 40A
Autosense power-on	in High level mode only
Overall efficiency	>60%

#### OUTPUT POWER RMS

Stereo power RMS @ 4Ω	250W x 2
Stereo power RMS @ 2Ω	340W x 2
Bridge power RMS @ 4Ω	680W x 1

#### SIGNAL INPUT

Input sensitivity range	0.35 ÷ 16V
Input impedance (High level mode)	470Ω (floating)
Input impedance (Low level mode)	10kΩ (ground referenced)
Input CMRR	> 80dB
Input interface configuration	fully differential

#### FEATURES

Onboard crossover filter configuration	OFF - LP - HP
HP and LP filter range	20 ÷ 225Hz
HP and LP filter slope	12dB/oct
G-CARD compatibility	All listed in the catalogue

#### CONNECTIONS

Low level input	RCA
High level input	RCA
Remote control RTC (optional)	Modular jack

#### APPEARANCE

Dimensions	310x200x50mm
Weight	2.5Kg
Color	Black
Finishing	Powder coating

#### COMPATIBLE ACCESSORIES:

G-CARDS  
RTC

