

SPL 3000c1



Specifications:

<i>Channels</i>	<i>no</i>	1
<i>Class</i>	<i>Typ</i>	D
<i>Power @14,4V /3.0% THD</i>		
<i>@ 4 ohm:</i>	<i>Wrms</i>	1000
<i>@ 2 ohm:</i>	<i>Wrms</i>	1850
<i>@ 1 ohm:</i>	<i>Wrms</i>	3100
<i>Operation supply</i>	<i>V</i>	10 -16
<i>Thermal protection</i>	<i>°C</i>	80
<i>THD @ 4 Ω / 50% Pmax</i>	<i>%</i>	0,1
<i>Signal/noise</i>	<i>dB</i>	71
<i>Efficiency (4 ohm)</i>	<i>%</i>	88
<i>Input sensitivity</i>	<i>Vrms</i>	0,2-6
<i>Low input impedance</i>	<i>Ω</i>	20 k
<i>Damping @ 80 Hz</i>		187
<i>Power consumption, idle</i>	<i>A</i>	3
<i>Power cons. 4 Ω</i>	<i>A</i>	78
<i>Power cons. 2 Ω</i>	<i>A</i>	156
<i>Weight</i>	<i>kg</i>	7,42
<i>Dimensions</i>	<i>l/w/h</i>	524/235/52 mm

Features:

- *Lowpass filter with 24 dB dB slope.*
- *Subsonic filter*
- *Phase shift 0 - 180°*
- *Bass adjust 0 – 12 dB*
- *Optional remote available*

Miscellaneous:

- Protection for overhead, over current, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink